

ND-4000B Gamma Area Monitor

- 120 VAC hard wired (or plug in)
- Non-adjustable trip point at 2 mR/hour.
- Will activate any 120 volt AC devices such as warning lights and sirens.
- Two 5 Amp 120 volt AC remote alarm outlets.
- One ac power on/off green indicator and one red alarm trip indicator.
- NEMA-3 steel case: 8"w x 8"h x 4"d
- Dimensions
- ND-4000B: 8"w x 9"h x 5"d. weight 6 pounds
- ND-4000BL: 8"w x 24"h x 5"d. weight 8.5 pounds
- ND-4000BLA: 8"w x 24"h x 5"d. weight 8.5 pounds
- Halogen quenched energy compensated gm tube, gamma and x-ray from 60-2000 kev +/- 20%.



Options:

Available in 110VAC and 230VAC (please specify if not 110VAC).

ND-4000BL – has built-in red rotating warning light mounted to top of unit.

ND-4000BLA – has built-in red rotating warning light mounted to top of unit and audio alarm



ND-AM1 - Portable red rotating light on stand with 25 foot power cord.

ND-AM2 – Portable red rotating light with and audio alarm stand with 25 foot power cord



DISTRIBUÉ PAR / DISTRIBUTED BY:



QUEBEC
164, St-Jean-Baptiste
Mercier, QC J6R 2C2
T : (450) 691-9090

ONTARIO
275 Sheldon Drive, Unit 3
Cambridge, ON N1T 1A3
T : (519) 894-9069

www.qnde.ca